

WEIGHTS AND DIMENSIONS (SUPPLEMENTAL DATA)

	Operating Weight	Tipping Load		Overall Width (Outside Tire)	Tread	Vertical Dimensions	Overall Length	
		Straight	Full Turn					
Remove ROPS Cab (for transport only)	lb (kg)	-1370 (-620)		in (mm)		-1'9 ¹¹ / ₁₆ " (-550)		
Remove Optional Counter Weight	lb (kg)	-900 (-410)	-2250 (-1020)	-1870 (-850)	in (mm)			
Air conditioner — Deletion	lb (kg)	-220 (-100)	-200 (-90)	-200 (-90)	in (mm)			
Belly Guard (Rear Frame)	lb (kg)	+510 (+230)	+860 (+390)	+750 (+340)	in (mm)			
Tires: 26.5-25-24PR (L-3)	lb (kg)	-930 (-420)	-710 (-320)	-620 (-280)	in (mm)	-3 ⁵ / ₈ " (-90)	-2" (-50)	+1 ⁵ / ₈ " (+40)
26.5-25-24PR (L-4)	lb (kg)	-45 (-20)	-45 (-20)	-22 (-10)	in (mm)	-2 ³ / ₈ " (-60)	-7 ⁷ / ₈ " (-20)	+7 ⁷ / ₈ " (+20)
26.5-25-24PR (L-5)	lb (kg)	+1260 (+570)	+950 (+430)	+840 (+380)	in (mm)	-2 ³ / ₈ " (-60)	-3 ³ / ₈ " (-10)	+3 ³ / ₈ " (+10)
29.5-25-22PR (L-4)	lb (kg)	+1610 (+730)	+1215 (+550)	+1080 (+490)	in (mm)	+3 ³ / ₈ " (+10)	+1 ³ / ₈ " (+35)	-1 ¹ / ₄ " (-30)
29.5-25-22PR (L-5)	lb (kg)	+2380 (+1080)	+1810 (+820)	+1590 (+720)	in (mm)	+3 ³ / ₈ " (+10)	+1 ⁵ / ₈ " (+40)	-1 ⁵ / ₈ " (-40)
26.5-25-24PR (L-3) (75% CaCl ₂)	lb (kg)	+2160 (+980)	+3990 (+1810)	+3530 (+1600)	in (mm)	-3 ⁵ / ₈ " (-90)	-2" (-50)	+1 ⁵ / ₈ " (+40)
29.5-25-22PR (L-3) (75% CaCl ₂)	lb (kg)	+4190 (+1900)	+6370 (+2890)	+5620 (+2550)	in (mm)			

Base Tire 29.5-25-22PR (L-3)

Tread 8³/₁₆" (2440mm)
 Width (outside tire) 10⁶/₄" (3220mm)
 Width (outside bucket) 11³/₈" (3450mm)

Equipped with GSC bucket with bolt on cutting edge

29.5-25-22PR (L-3) Tire and ROPS Cab

